


# Powerhook Order Transmittal and Check Sheet

(Note: Items below listed in **bold text** are subject to additional charge if not included in original quote)

<b>Bill To:</b>		<b>Salesman:</b>	
		<b>Office Phone:</b>	
		<b>Office Fax:</b>	
Date Entered	PO #	Requested Ship Date:	Shipping Instructions:
Ship to Customer	Quantity	Carrier:	<input type="checkbox"/> Prepaid
Ship to Address	Restraint:	Quote #:	<input type="checkbox"/> Collect
Ship to Address 1	Dock Leveler Model:	Phone #:	<input type="checkbox"/> Third Party
Ship to Address 2	Capacity:	Comments:	
<b>Restraint Information – REQUIRED</b>			
Communication Lights: <input type="checkbox"/> LED Inside/Incandescent Outside (Standard) <input type="checkbox"/> <b>All Incan Lights</b> <input type="checkbox"/> <b>Incandescent Inside/LED Outside</b> <input type="checkbox"/> <b>All LED Lights</b>		The area where the hook pan is to be installed needs to be free from obstruction. From the front wall to the rear of the pan measures 48" after it has been poured in place. The pan width after it has been poured in place is 13". There can not be any obstructions by house cylinder trunnions, hold down assemblies, or any cross member in the area described. Please see drawing below: 	
<b>Optional Extras</b> <input type="checkbox"/> Interlock Terminal (For extra leveler or door switch) <input type="checkbox"/> Auto Raise Feature (Lip to Grade) <input type="checkbox"/> Low Profile Design			
<b>Note: There are 17 wires coming into this box. It needs to be of sufficient size to accommodate. The recommended size box is 6" x 6". If Junction Box is not available, conduit can be run through front of leveler.</b>			
The hook at the resting state needs to be approximately 28" off grade. Is there enough room for the Powerhook to operate and capture an ICC bar at approximately 28" off grade without hitting the dock leveler lip on the unstroke first before contacting the ICC bar?			
The pump, motor and valve assembly can be pit mounted or wall mounted.		Notes:	
The Powerhook can be successfully retrofit by offsetting the unit 14" off center beneath competitor mechanical units with center springs.			
<b>Pit Information - REQUIRED</b>			
Make & Model of Leveler	Pit Depth (Front of Pit)		
Dock Height	Pit Length	Pit Width	
<b>Lip/Bumper Information – REQUIRED</b>			
Lip Length: <input type="checkbox"/> 16" <input type="checkbox"/> Barrier Lip <input type="checkbox"/> 18" <input type="checkbox"/> 5" <input type="checkbox"/> 20" <input type="checkbox"/> 7" <input type="checkbox"/> Other		Bumper Projection:	
<b>Dock Conditions - REQUIRED</b>			
Dock Face Design (vertical and plumb) <input type="checkbox"/> Yes <input type="checkbox"/> No		Dock Face Construction Material Thickness	
Drive Construction Material Thickness			
Drive Approach (Check One)	<input type="checkbox"/> Level <input type="checkbox"/> Decline <input type="checkbox"/> Incline <input type="checkbox"/> Split--describe	% of Slope	
Does the drive have any drains or other obstructions? <input type="checkbox"/> Yes <input type="checkbox"/> No			
Voltage and Phase			
Size of Junction Box at Rear Pit Wall			
			Notes:
For additional loading dock, construction and safety items go to <a href="http://www.alliedproductsolutions.com">www.alliedproductsolutions.com</a> .			
Additional Notes:			Net price each: \$  Total net price: \$