Divisions of Systems	PDLM				Power® ecklist	
<u>Customer</u> :	Order #:	-		Date:		
Address:	Equipment Model:					
	controls before installing or operating e	er's/User's Manual and become thoroughly familiar with the equipment and its equipment. Failure to read and understand the owner's/user's manual could age to equipment or voiding of warranty!				
Maintenance Steps		Dock #	Dock #		Dock #	Dock #
		Serial #	Serial #		Serial #	Serial #
Quarterly M	aintenance					
 Check fluid level. Make sure to prepare equipment for fluid level check. Pit Levelers (with or without transport vehicle restraints) must be in the below-dock position. Vertical Storing Levelers (with or without transport vehicle restraints) must be in the stored position. 						
2) Turn OFF all electrical power to the pump station.						
3) Open the cover and remove the fill cap.						
4) Add hydraulic fluid if necessary. Use only recommended fluid (reference owner's manual). Fluid level should be between min and max lines.						
5) Reinstall fill cap and close the cover.						
6) Turn on power to the pump station and return all equipment to the stored position.						
Biannual maintenance						
1) Change oil filter. Part# 9391-0082.						
2) Users that only need one pump motor for operation should use the selector switch (see Figure 24) to change motors every six months. This will balance component wear and extend pump station life. If a pump motor fails, the remaining pump motor can then be used to prevent facility downtime.						

Annual Maintenance		
1) Complete quarterly and bi-annual maintenance.		
2) Change hydraulic oil. (may be required more often depending on environment)		

Dock#	Comment or Description of Repair(s) Needed	Approval	Completed

Notes: (Detail adjustments performed, parts replaced, etc.) _____

By signing below I/we certify that all steps required by Systems, LLC have been completed:

Service Provider Representative (print name & sign):	Date:
Customer/End User Representative (print name & sign):	Date:



Recommended Spare Parts

CentraPower

Quantity	Part Number	Description
1	9301-0009	Suction Screen/ Strainer
1	9391-0082	Oil Filter, Spin-on
1	8512-0002	5 Gal Hydraulic Oil. Meets MIL-H-5606 G