(Note: Items below listed in bold text are subject to additional charge if not included in original quote) Office Phone: Salesman: INFORMATION IN THIS SECTION IS REQUIRED TO VALIDATE EQUIPMENT WARRANTY ☐ Retail Distribution Bill To Address: Ship To Address: **End User Address:** End User Type: .com ☐ Retail Stores Aero/Auto Transportation ☐ Consumer ☐ Pharm/Medical ☐ Developer ☐ Warehouse ☐ Food/Beverage ☐ Stock ☐ Government ☐ Farming ☐ Grocery Distribution ☐ Technology Grocery Retail ☐ Service ☐ Industrial ☐ Entertainment PO# Requested Ship Date: Shipping Instructions: Flatbed Required Quantity Carrier: ☐ Prepaid Quote #: ☐ Collect Restraint Model Van Required Comments: Phone #: Third Party Are lifting lugs required for installation? ☐Yes ☐ No Leveler Size - REQUIRED **Leveler Capacity - REQUIRED** ☐ 6'W X 6'L ☐ 6'6" W X 6'L 7'W X 6'L 60,000 lbs CIR □ 6'W X 8'L ☐ 6'6 W X 8'L □ 7'W X 8'L 30,000 lbs CIR 45,000 lbs CIR ☐ 6'W X 10' L ☐ 6'6" W X 10'L ີ່ 7'W X 10'L 35,000 lbs CIR 50,000 lbs CIR Pit Information - REQUIRED ■ New Loading Dock Area Notes: □ Existing Loading Dock Area Right Rear Right Front Pit Width Cut down in Width? Left Rear Left Front Pit Length Cut down in Length? ☐ Cut down Depth? Filler To Be Provided By Systems **Misc Metals Curb Angles** Pans Curb Angle to ship early 3 Sided Pans to ship early 🗌 **Date Required** Date Required ☐ 3 Sided Pan ☐ 6 Piece Angle 4 Piece Angle/ 2 piece bumper plate 4 Sided Pan Per Systems, Inc. pit detail unless otherwise noted ☐ Squaring Kit Bumper Plate Weldments Lip/Bumper Information - REQUIRED 16" Lip Length: ☐ Barrier Lip ☐ Max Bevel **] 18**" Standard is 4-1/2" x 10" x 14" □ 5" ☐ Reduced Lip Crown □ 7" 20" Other INFORMATION IN THIS SECTION REQUIRED TO VALIDATE EQUIPMENT WARRANTY Max Gross Moving Load Dock Height # of Shifts Notes: Fork Trucks ☐ 3 Wheel Required Service Range Required Service Range 4 Wheel Above Below ☐ 3 Wheel Offset/Standup Incline Drive Level Drive **Decline Drive** % If drive is decline / incline please explain how this is being handled. Electrical - Required Frame/Finish Information - Required Notes: **Electrical Voltage and Phase Abrasive Deck Auto Return to Dock** Abrasive Lip **Special Color Paint (Provide Sample) Emergency Stop Smooth Deck Plate Quick Cycle Lip (Lip Out)** Combo Lip Out/E-Stop Smooth Lip Plate **Disconnect Switch Spray Metalize Overhead Door Buttons Hot Dip Galvanize** (Only available on units 45k and above) **Remote Mount Powerpack Optional Extras Restraint Information** Notes: **Brush Weatherseal (Rear Brush)** Restraint Engaged Interlocking (Restraint Rubber Weatherseal (Rear Foam engaged or unit placed in bypass mode Insulation allows leveler to operate) **Stainless Steel Hinge Pins** Leveler Stored Interlocking (Lip Prox) **Grease Fittings (Every tube)** (Leveler stored allows restraint to be released) Audible Alarm Key Switch For additional loading dock, construction and safety items go to www.alliedproductsolutions.com.